

SYNNESTVEDT & LECHNER LLP

AMENDMENTS TO THE CLAIMS

This Listing of Claims will replace all prior versions, and listings, of claims in this application.

Listing of Claims:

1-21. (Canceled)

22. (Currently Amended) A pencil sharpener comprising:

a first longitudinally elongated external shell having internal ribs defining a first plurality of support surfaces;

a plurality of discrete components, said plurality of discrete components comprising a sharpening sub-assembly, said plurality of discrete components being capable of being assembled to provide a pencil sharpening assembly operable for sharpening a pencil;

a second longitudinally elongated external shell mated with said first external shell to define a substantially closed compartment, said second external shell having internal ribs defining a second plurality of support surfaces;

wherein each support surface extends along an edge of a respective internal rib, and wherein said first and second pluralities of support surfaces cooperate with each other to laterally position and fixedly retain said discrete components sharpening sub-assembly within said shells, at least one of said support surfaces positioning and supporting at least one of said discrete components in a predetermined operative spatial relationship relative to another of said discrete components that is separately positioned and supported by another of said support surfaces.

SYNNESTVEDT & LECHNER LLP

23. (Currently Amended) The pencil sharpener of claim 22, wherein said first and second pluralities of support surfaces serve as the sole means of mounting said plurality of discrete components sharpening sub-assembly in said compartment.

24. (Currently Amended) ~~The pencil sharpener of claim 22, wherein~~ A pencil sharpener comprising:  
a first longitudinally elongated external shell having internal ribs defining a first plurality of support surfaces;  
a sharpening sub-assembly for sharpening a pencil, said sharpening sub-assembly comprising comprises:

a blade-supporting shaft;

a rotary blade and a pinion supported co-axially on said blade-supporting shaft, said rotary blade having spiral cutting edges;

a blade holder defining a cavity for receiving an end of the said pencil therein and supporting said blade-supporting shaft, said blade holder being supported by said first and second external shells to be rotatable around an axis of said cavity;

a cutter gear module defining a pencil-receiving opening and including an annular ring gear meshing with said pinion; and

a drive shaft which drives said blade holder around said axis; and  
a second longitudinally elongated external shell mated with said first external shell to define a substantially closed compartment, said second external shell having internal ribs defining a second plurality of support surfaces;

wherein each support surface extends along an edge of a respective internal rib, and wherein said first and second pluralities of support surfaces cooperate with

SYNNESTVEDT & LECHNER LLP

each other to laterally position and fixedly retain said sharpening sub-assembly within said shells; and

wherein said drive shaft is capable of driving said blade holder around said cavity, causing said pinion to travel along said annular ring gear and said rotary blade to rotate and sharpen the pencil advanced into said cavity.

25. (Original) The pencil sharpener of claim 24, wherein said blade holder defines a ring flange and said cutter gear module defines a ring groove for registering with said ring flange; and

wherein said blade holder is rotatably supported at one end by said cutter gear module when said ring flange is positioned within said ring groove, said cutter gear module being supported by said first and second external shells.

26. (Currently Amended) The pencil sharpener of claim 22, the plurality of discrete components further comprising:

an electric motor operatively connected to said sharpening sub-assembly for driving said sharpening sub-assembly, ~~said first and second pluralities of support surfaces cooperating with each other to engage and retain said electric motor in response to mating of said first and second external shells, said first and second pluralities of support surfaces serving as the sole means of mounting said electric motor in said compartment.~~

27. (Original) The pencil sharpener of claim 24, further comprising:

an electric motor operatively connected to said sharpening sub-assembly for driving said sharpening sub-assembly, said first and second pluralities of support

SYNNESTVEDT & LECHNER LLP

surfaces cooperating with each other to engage and retain said electric motor in response to mating of said first and second external shells, said first and second pluralities of support surfaces serving as the sole means of mounting said electric motor in said compartment;

wherein said motor gear module comprises a switch operatively connected to said electric motor for driving said sharpening sub-assembly when said switch is activated upon insertion of the pencil into said pencil-receiving opening.

28. (Original) The pencil sharpener of claim 27, wherein said switch comprises a pawl and a pair of contacts mounted on said cutter gear module, said pawl being positioned to cause said pair of contacts to electronically connect for closing a circuit.

29. (Original) The pencil sharpener of claim 24, wherein said cutter gear module comprises: a switch operatively connected to said electric motor for preventing operation of said motor unless said switch is activated by mating of a receptacle with said first and second external shells.

30. (Original) The pencil sharpener of claim 29, wherein said switch comprises a pawl and a pair of contacts mounted on said cutter gear module, said pawl being positioned to cause said pair of contacts to electronically connect for closing a circuit.

31. (Previously Presented) The pencil sharpener of claim 24, further comprising:

SYNNESTVEDT & LECHNER LLP

a dual switch operatively connected to said electric motor for driving said sharpening sub-assembly only when said dual switch is activated by a pencil inserted into said pencil-receiving opening and by a receptacle mated with said first and second external shells.

32. (Original) The pencil sharpener of claim 31, wherein said dual switch comprises:

a first contact electrically connected to a first side of a circuit powering said electric motor;

a second contact electrically connected to a second side of said circuit;

a third contact mounted in spaced relationship to said first and second contacts;

a first pawl mounted on said cutter gear module in position to cause said third contact to electrically connect with said first contact responsive to insertion of a pencil into said pencil-receiving opening; and

a second pawl mounted on said cutter gear module in position to cause said third contact to electrically connect with said second contact responsive to mating of a receptacle with said first and second external shells.

33. (Original) The pencil sharpener of claim 32, further comprising a receptacle removably matable with said first and second external shells for receiving pencil shavings discharged from said sharpening sub-assembly.

34. (Original) The pencil sharpener of claim 33, wherein said receptacle comprises an internal fin positioned to contact said second pawl of said dual switch.

SYNNESTVEDT & LECHNER LLP

35. (Currently Amended) A pencil sharpener comprising:

- a first external shell having internal ribs defining a first plurality of support surfaces;
- a cutter assembly defining a ring flange and having a rotatable pinion;
- a ~~cutter~~ gear module defining a pencil-receiving opening and including an annular ring gear meshing with said pinion, said gear module defining a ring groove for registering with said ring flange;
- a second external shell mated with said first external shell to define a substantially closed compartment, said second external shell having internal ribs defining a second plurality of support surfaces;
- whereby said cutter assembly is rotatably supported at one end by said gear module when said ring flange is positioned within said ring groove;
- wherein each internal rib comprises a first side and a second side opposite said first side, each of said first and second sides adjoining one of said first and second external shells, each of said first and second pluralities of support surfaces extending between a respective first and second side of a respective rib; and
- wherein said first and second pluralities of support surfaces cooperate with each other to engage and retain said cutter assembly and said gear module in said compartment, at least one of said support surfaces positioning and supporting said cutter assembly in a predetermined operative spatial relationship relative to said gear module, said gear module being separately positioned and supported by another of said support surfaces.

SYNNESTVEDT & LECHNER LLP

36. (Original) The pencil sharpener of claim 35, wherein said first and second pluralities of support surfaces serve as the sole means of mounting said cutter assembly and said gear module in said compartment.

37. (Original) The pencil sharpener of claim 35, wherein said cutter assembly comprises:

a blade-supporting shaft;

a rotary blade carried co-axially on said blade-supporting shaft, said rotary blade having spiral cutting edges;

a blade holder defining a cavity for receiving an end of a pencil therein and supporting said blade-supporting shaft, said blade holder being supported by said first and second external shells to be rotatable around an axis of said cavity; and

a drive shaft which drives said blade holder around said axis;

wherein said pinion is carried co-axially on said shaft;

whereby said blade holder is rotatably supported at one end by said gear module when said ring flange is positioned within said ring groove, said gear module being supported by said first and second external shells; and

whereby said drive shaft is capable of driving said blade holder around said cavity, causing said pinion to travel along said annular ring gear and said rotary blade to rotate and sharpen any pencil advanced into said cavity.

38. (Previously Presented) The pencil sharpener of claim 37, further comprising:

a dual switch operatively connected to said electric motor for driving said sharpening sub-assembly only when said switch is activated by a pencil inserted into

SYNNESTVEDT & LECHNER LLP

said pencil-receiving opening and by a receptacle mated with said first and second external shells.

39. (Original) The pencil sharpener of claim 38, wherein said dual switch comprises:

a first contact electrically connected to a first side of said circuit powering said electric motor;

a second contact electrically connected to a second side of a said circuit;

a third contact mounted in spaced relationship to said first and second contacts;

a first pawl mounted on said cutter gear module in position to cause said third contact to electrically connect with said first contact responsive to insertion of a pencil into said pencil-receiving opening; and

a second pawl mounted on said cutter gear module in position to cause said third contact to electrically connect with said second contact responsive to mating of a receptacle with said first and second external shells.

40. (Original) The pencil sharpener of claim 39, further comprising:

an electric motor operatively connected to said cutter assembly for driving said cutter assembly, said first and second pluralities of support surfaces cooperating with each other to engage and retain said electric motor in said compartment when first and second external shells are mated, said first and second pluralities of support surfaces serving as the sole means of mounting said electric motor in place in said compartment; and



SYNNESTVEDT & LECHNER LLP

a receptacle removably matable with said first and second external shells for receiving pencil shavings discharged from said sharpening sub-assembly.

41. (Original) The pencil sharpener of claim 40, wherein said receptacle comprises an internal fin positioned to contact said second pawl of said dual switch.

42. (Currently Amended) A method of manufacturing a pencil sharpener, comprising:

providing a plurality of discrete internal sharpener components, said sharpener components including a cutter assembly capable of sharpening a pencil and an electric motor for driving said cutter assembly;

providing a longitudinally elongated first external shell, said first shell having internal ribs defining a first plurality of support surfaces configured to be capable of laterally supporting said sharpener components, each support surface extending along an edge of a respective internal rib;

providing a longitudinally elongated second external shell matable with said first external shell to form a housing of said pencil sharpener when so mated, said second shell having internal ribs defining a second plurality of support surfaces, each support surface extending along an edge of a respective internal rib, said second plurality of support surfaces being capable of cooperating with said first plurality of support surfaces to laterally support and fixedly retain said ~~internal~~ sharpener components within said housing when said first and second shells are mated;

placing said ~~internal~~ sharpener components on said first external shell such that said sharpener components are laterally supported by said internal ribs of said first external shell, at least one of said support surfaces positioning and supporting

SYNNESTVEDT & LECHNER LLP

said cutter assembly in a predetermined operative spatial relationship relative to said electric motor, said electric motor being separately positioned and supported by another of said support surfaces; and

        mating said second external shell to said first external shell to complete said housing and fix said internal sharpener components therein.

43-44. (Canceled)

45.     (Previously Presented) The pencil sharpener of claim 22, wherein each of said internal ribs comprises a first side and a second side opposite said first side, said first and second sides adjoining one of said first and second external shells, and wherein each of said support surfaces extends between respective first and second sides of a respective internal rib, said support surfaces cooperating to engage said sharpening sub-assembly.

46.     (Previously Presented) The pencil sharpener of claim 35, wherein each of said first and second external shells is elongated in a longitudinal direction, and wherein said first and second pluralities of support surfaces cooperate with each other to laterally position said cutter assembly and said gear module in said compartment.

47.     (New) The pencil sharpener of claim 22, wherein said support surfaces are configured to position and support said discrete components in mechanically interengaging positions that provide for operability of said operable pencil sharpening assembly.